

State Wide Striping Contract Available to Oklahoma Municipalities

By James Montgomery, ODOT

(Continued from page 9)

Table 2 shows when to use thermoplastic stripe and the thickness to be used based on volume:

THERMOPLASTIC STRIPE POLICY

Partial Controlled Access Facilities (2 lanes or more)

Asphalt Surfaces*	4" white lane lines 4" yellow and 4" white edge lines
-------------------	--

2 Lane Highways

Asphalt Surfaces*	4" yellow center lines 4" white edge lines
-------------------	---

*For ADT's of 5000 or greater, standard thickness (120 mils), hot-applied thermoplastic shall be used; for ADT's less than 5000 and greater than 2500, thin-line (70 mils) thermoplastic stripe shall be used; for ADT's less than 2500, waterborne paint shall be used.

Also, the contract has pay items for R/R symbols, arrows, words, STOP bars and other pavement marking needs. The contract also has special provisions for minimum retro-reflective for both thermoplastic and multi-polymer pavement markings. This assures the municipalities and the counties that the stripe will be reflect for nighttime driving.

The current contractor for the statewide striping contract is Action Safety Supply Company. You may contact Mr. Jerry Hietpas at 405.787.2244 to discuss what your needs are for your municipality or county. You may also look at the statewide striping contract at the Department of Central Services website at www.ok.gov/DCS. Click on Central Purchasing then Statewide contracts and then click on SW 776 to look at the prices for pavement markings or go the OTEA website to see the contract. For further information, contact James Montgomery, Oklahoma Department of Transportation, at 405.521.4302.

MUTCD Pavement Marking Standards

CHAPTER 3B. PAVEMENT AND CURB MARKINGS

Section 3B.01 Yellow Center Line Pavement Markings and Warrants

Standard:

- 01 Center line pavement markings, when used, shall be the pavement markings used to delineate the separation of traffic lanes that have opposite directions of travel on a roadway and shall be yellow.
- 09 Center line markings shall be placed on all paved urban arterials and collectors that have a traveled way of 20 feet or more in width and an ADT of 6,000 vehicles per day or greater. Center line markings shall also be placed on all paved two-way streets or highways that have three or more lanes for moving motor vehicle traffic.

